BioProtect

INDUSTRIAL TREATMENT

ELIMINATE F.O.G. (FATS, OILS, GREASE) AND ORGANIC MATERIAL

REDUCES BUILD UPS & ODOURS

NON-TOXIC FORMULA





Penetrates hard to reach places in industrial applications, including sewers, grease traps and sludge ponds to prevent blockages caused by fats, oil, grease and organic wastes. It also controls ammonia, hydrogen sulphide and other offensive odours as well as reducing pathogens like E-Coli.

PRODUCT BENEFITS



This non-toxic, non-corrosive and eco-friendly formula removes blockages and odours in drains, pipes, sewers, grease traps, sludge pond and more. It also has asset longevity benefits by reducing sludge loads in oxidation and settling ponds, reduces corrosive effects on concrete steel & equipment caused by hydrogen sulphide. You will also benefit from reduced maintenance cost associated with F.O.G. blockages and sewer pump loads.

WHERE TO USE



- Created specifically for use in the following areas:
- Sewers
- Sludge Ponds
- Waste Water Facilities
- Grease TrapsPipes
- Pipes
 Industrial [
- Industrial Bins & Chutes
- Drains
- Rendering Facilities
- Landfill Sites

TECHNICAL SPECIFICATIONS

COLOUR: LIGHT TAN

pH:5.5>6.5

ODOUR: FAINT YEAST

CLEANER SPACES, HEALTHIER PEOPLE visit <u>au.bioprotect.bio</u> for more



Australian Owned

HOW TO DILUTE



Dosage rates vary according to the application and areas of use. Typical dosage rates for waste water are between 500-1000ppm

DIRECTIONS FOR USE



Contact your supplier for instructions specific to your facility or use.

SAFETY & PPE



PPE: Safety glasses and gloves may be worn.Safety: Always take care when handling any chemicals. Refer to the SDS for additional Information at au.bioprotect.bio



CLEANER SPACES, HEALTHIER PEOPLE visit <u>au.bioprotect.bio</u> for more

